built: 1-11-07 OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION $\frac{9}{10 + 15 + 10}$ TOWNSHIP $\frac{14}{10 + 15 + 10}$ RANGE ____5 P 2 DATE: __ PARTY CHIEF: Wilcoxen Indian Ck 6500 S CREW: TYPE OF MARKER: Harrison METHOD OF ESTABLISHMENT: County: 8-1-98 IN. S.P.C. E ZONE NAD '83 0 14050905 NAME: L. 491466.2170(m) N: 73088.5224(m) E :: NOTE: This corner position represents a title corner and may not necessarily be in the position of the Section Line 10500 Record corner. Indian Creek 6500 S 96.71 170.49' 1. PWP

A survey by Hosbrook 3-10-1852 called no stone but witness: 5" beech N 13 E $18 \ 1/2 \ \text{links}$, 6" elm N 15 W 38 links per Franklin Township Legal Survey Book pg. 36. $7-22-64 \ \text{MCSO}$ called an iron pin. Wilcoxen 2-6-80 called railroad spike. Wilcoxen 9-12-86 called same. Greene 10-29-89 called railroad spike. with cut 'x'. Kiste 1-7-94 called same. Excavated by Wilcoxen 8-1-98 and railroad spike found 2" down. Stone found 8" down under railroad spike. Harrison set. Re-tied 10-15-02 by Wilcoxen.

	_	-	_	_	0	-
14	()	5	()	9	()	5

Note: new school being

1100	30303	
REF.	DISTANCE	DESCRIPTION
1.	170.49	Mag nail w/brass washer N PwP#50-771 D 6"up
2.	96.71	Mag nail w/brass washer N PwP# 49-771 C